



10/801840

PATENT  
Attorney Docket No. 4329.3270

*cofe*

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re U.S. Patent No.: 7,187,775 B2 )  
)  
Inventor: Atsushi Fujita )  
)  
Issue Date.: March 6, 2007 )  
)  
For: AUDIO SIGNAL RECORDING )  
APPARATUS )

**Certificate**  
MAR 23 2007  
**of Correction**

Commissioner for Patents  
P.O. Box 1450  
Alexandria, VA 22313-1450

Sir:

**REQUEST FOR CERTIFICATE OF CORRECTION**

Pursuant to 35 U.S.C. § 254, and 37 C.F.R. § 1.322, this is a request for a Certificate of Correction in the above-identified patent. The mistakes identified in the appended Form occurred through the fault of the Patent Office, as clearly disclosed by the records of the application which matured into this patent.

Two (2) copies of PTO Form 1050 are appended. The complete Certificate of Correction involves one (1) page. Issuance of the Certificate of Correction containing the correction is earnestly requested.

Please charge any required fees not included herewith to Deposit Account 06-0916.

Respectfully submitted,

FINNEGAN, HENDERSON, FARABOW,  
GARRETT & DUNNER, L.L.P.

Dated: 3/21/2007

By: Richard V. Burgujian Reg. No. 31,744  
53,235, p. 1

MAR 23 2007

**UNITED STATES PATENT AND TRADEMARK OFFICE**  
**CERTIFICATE OF CORRECTION**

PATENT NO. 7,187,775 B2

Page 1 of 1

APPLICATION NO.: 10/801,840

ISSUE DATE: March 6, 2007

INVENTOR: Fujita

It is hereby certified that an error or errors appear in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

Claim 5, column 6, line 27, change "detection result;" to --detection result, wherein the detected voltage of one of the right and left signal channel terminals is a voltage of the power supplied to the microphone resistance-divided by a power supply resistance and an internal resistance of the corresponding one of a right and left channel of the microphone, when a stereo microphone is connected to the microphone input terminal; and--.

Claim 5, column 6, line 30, change "result," to --result.--, then delete the remainder of the paragraph.

**MAILING ADDRESS OF SENDER**

Finnegan, Henderson, Farabow,  
Garrett & Dunner, L.L.P.  
901 New York Avenue, N.W.  
Washington, D.C. 20001-4413

**MAR 23 2007**

**UNITED STATES PATENT AND TRADEMARK OFFICE**  
**CERTIFICATE OF CORRECTION**

PATENT NO. 7,187,775 B2

Page 1 of 1

APPLICATION NO.: 10/801,840

ISSUE DATE: March 6, 2007

INVENTOR: Fujita

It is hereby certified that an error or errors appear in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

Claim 5, column 6, line 27, change "detection result;" to --detection result, wherein the detected voltage of one of the right and left signal channel terminals is a voltage of the power supplied to the microphone resistance-divided by a power supply resistance and an internal resistance of the corresponding one of a right and left channel of the microphone, when a stereo microphone is connected to the microphone input terminal; and--.

Claim 5, column 6, line 30, change "result," to --result.--, then delete the remainder of the paragraph.

**MAILING ADDRESS OF SENDER**

Finnegan, Henderson, Farabow,  
Garrett & Dunner, L.L.P.  
901 New York Avenue, N.W.  
Washington, D.C. 20001-4413

**MAR 23 2007**